

ABN 98 000 869 367

SAFETY DATA SHEET

ISSUED DATE: 15th November 2016

Revision Date 25-Oct- 2016

Version 1

Section 1: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Identifier

Product Name **Neutral Brush Plastigel/Gelcoat**

Other means of identification

UN Number **UN1866**

Recommended use of the chemical and restrictions on use.

Recommended Use **Recommended for Industrial and/or Professional use only**

Details of Distributor

Fiberglass (A/Asia) Sales Pty. Ltd.
2 Lincoln Street,
Minto NSW 2566

For further information, please contact

Contact Point Phone: (02) 9820 1144

Email: info@fiberglass-sales.com.au

Emergency Phone: (02) 9820 1144 (Business Hours)

Section 2: HAZARD(S) IDENTIFICATION

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG)

Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonised System (GHS)

GHS Classification

Flammable liquids	Category 3 - (H226)
Acute toxicity - Oral	Category 4 -(H302)
Acute toxicity -Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1 - (H317)
Carcinogenicity	Category 1A -(H350)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)

Label elements



Signal word

Danger

Hazard statements

H226 - Flammable liquid and vapour
 H302 - Harmful if swallowed
 H332 - Harmful if inhaled
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H317 - May cause an allergic skin reaction
 H350 - May cause cancer
 H361 - Suspected of damaging fertility or the unborn child
 H335 - May cause respiratory irritation
 H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Do not breathe dust/fume/gas/mist/vapours/spray
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ ventilating/ lighting/ equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 Specific treatment (see supplemental first aid instructions on this label)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before re-use
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Rinse mouth
 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Harmful to aquatic life with long lasting effects
 Toxic to aquatic life
 This product contains crystalline silica (quartz) in a non-repairable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product
 Avoid dust formation
 Sanding and grinding dust may be harmful if inhaled

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**Substance**

Not applicable

Chemical Name**CAS No****Weight-%**

Styrene	100-42-5	30-<60
Kaolin	1332-58-7	10-<25
Titanium dioxide	13463-67-7	10-<20
Diethylene glycol	111-46-6	10-<20
Talc	14807-96-6	10-<20
Methyl Methacrylate	80-62-6	5-<10
Silica gel, precipitated, crystal free	112926-00-8	1-<5

Fumed Silica	112945-52-5	1-<3
2-Hydroxyethyl methacrylate	868-77-9	1-<3
Silica, Amorphous	7631-86-9	1-<3
Cobalt octoate	136-52-7	<0.3
Crystalline silica	14808-60-7	<0.3
2-Hydroxy-4-methoxybenzophenone	131-57-7	<0.3
Dicocodimethylammonium chloride	61789-77-3	<0.3
Non-hazardous ingredients	Balance	

Section 4: FIRST AID MEASURES

Description of first aid Measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. IF exposed or concerned: Get medical advice/attention.
Emergency telephone number	Poisons Information Centre, Australia: 13 11 26
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur.
Skin contact	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Get medical attention if irritation develops and persists. Wash off immediately with soap and plenty of water for at least 15 minutes.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Burning sensation.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances
------------------------	---

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media Carbon dioxide (CO₂). Dry chemical. Alcohol resistant foam. Water spray.

Unsuitable extinguishing media Do not use water jet stream.

Specific hazards arising from the chemical

In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact. Thermal decomposition can lead to release of irritating and toxic gases and vapours. Flammable. Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.

Special protective actions for fire-fighters

Wear self-contained breathing apparatus and protective suit. Use personal protective equipment as required.

Hazchem code •3Y.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up**Methods for containment**

Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up.

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards**Prevention of secondary hazards**

Clean contaminated objects and areas thoroughly observing environmental regulations.

Reference to other sections

See section 8 for more information. See section 13 for more information.

Section 7: HANDLING AND STORAGE**Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before re-use. Remove contaminated clothing and shoes.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash hands before breaks and immediately after handling the product. Wash hands before breaks and after work. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e. pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep out of the reach of children. Store locked up. Store away from other materials. Hazardous polymerisation may take place during a fire due to heat. Closed containers could violently rupture. Do not store at temperatures above 27C.

Incompatible materials

Strong acids. Strong bases. Strong oxidising agents.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure Limits**

This product, as supplied, contains hazardous materials with occupational exposure limits.

Chemical Name	Australia
Styrene 100-42-5	50 ppmTWA 213 mg/m ³ TWA 100 ppm STEL 426 mg/m ³ STEL
Kaolin 1332-58-7	10 mg/m ³ TWA
Titanium dioxide 13463-67-7	10 mg/m ³ TWA
Diethylene glycol 111-46-6	23 ppmTWA 100 mg/m ³ TWA
Talc 14807-96-6	2.5 mg/m ³ TWA
Methyl Methacrylate 80-62-6	50 ppm TWA 208 mg/m ³ TWA 100 ppm STEL 416 mg/m ³ STEL
silica gel, precipitated, crystal free 112926-00-8	10 mg/m ³ TWA
Silica, Amorphous 7631-86-9	2 mg/m ³ TWA
Crystalline silica 14808-60-7	0.1mg/m ³ TWA

Biological occupational exposure limits

An occupational medicine specialist familiar with national and regional regulations and standards must be consulted to establish a program of medical examinations for workers exposed to substances with biological limit values

Chemical Name	Australia	ACGIH	United Kingdom	European Union
Styrene 100-42-5	-	Mandelic acid plus phenylglyoxylic acid: 400 mg/g creatinine urine end of shift Styrene: 40 µg/L urine end of shift	-	

Appropriate engineering controls

Engineering Controls Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Face protection shield.
Skin and body protection Antistatic footwear. Wear fire flame resistant/retardant clothing. Gloves made of plastic or rubber. Suitable protective clothing. Apron.

Respiratory protection Where respiratory protection is required, use a respirator selected and in accordance with AS/NZS 1715 and AS/NZS 1716.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid
Appearance Hazy
Colour Clear
Odour Pungent
Odour threshold No information available

Property	Values	Remarks • Method
pH		Not applicable
Melting point / freezing point		No information available
Boiling point / boiling range	145°C	(based on components)
Flash point	27°C	Tag Closed Cup
Evaporation rate	0.49	
Flammability (solid, gas)		No information available
Flammability Limit in Air		
Upper flammability limit:	6.1%	
Lower flammability limit:	1.1%	

Neutral Brush Plastigel/Gelcoat

Revision Date 25-Oct- 2016

Vapour pressure	6	hPa, 20°C Derived from solvent
Vapour density	3.6	Derived from solvent
Relative density	0.95	
Water solubility		Insoluble
Solubility(ies)	-	No information available
Partition coefficient		No information available
Autoignition temperature		No information available
Decomposition temperature		No information available
Kinematic viscosity	316mm ² /s	
Dynamic viscosity	> 300mPa s	No information available
Explosive properties	No information available	
Oxidising properties	Not applicable	

Other Information

VOC Content (%)	Not applicable
Density	No information available
• This information may be derived from the components in the preparation.	

Section 10: STABILITY AND REACTIVITY

Reactivity No Data Available.

Chemical stability Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None
Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

Possibility of Hazardous Reactions

HAZARDOUS POLYMERISATION MAY OCCUR UPON DEPLETION OF INHIBITOR.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong bases. Strong oxidising agents.

Hazardous Decomposition Products

Decomposition products can include and are not limited to: Styrene.

Section 11: TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Irritating to eyes. (based on components). Causes serious eye irritation.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document
Converted acute toxicity point estimates may have been used when only acute toxicity hazard classification is available.

ATEmix (oral)	1,430.00
ATEmix (dermal)	82,543.00
ATEmix (inhalation-vapour)	27.00
ATEmix (inhalation-dust/mist)	3.70
0 of the mixture consists of ingredient(s) of unknown toxicity	

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene	= 1000 mg/kg (Rat)	-	= 11.7 mg/L (Rat) 4 h
Diethylene glycol	= 12565 mg/kg (Rat)	- 11890 mg/kg (Rabbit)	-
Methyl Methacrylate	= 7900 mg/kg (Rat) = 7872 mg/kg (Rat)	-	- 4632 ppm (Rat) 4 h
Fumed Silica	= 3160 mg/kg (Rat)	-	-
2-Hydroxyethyl methacrylate	= 5050 mg/kg (Rat)	-	-
Crystalline silica	-	-	-
2-Hydroxy-4-methoxybenzophenone	= 7400 mg/kg (Rat)	-	-

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation

Classification based on data available for ingredients. Irritating to eyes.

Sensitisation

May cause sensitisation by skin contact.

Germ cell mutagenicity

No information available.

Carcinogenicity

Reproductive toxicity

Contains a known or suspected reproductive toxin.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure

Aspiration hazard

May be fatal if swallowed and enters airways.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Unknown Aquatic Toxicity 0.07638083 of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Fish
Styrene	19.03 - 33.53 mg/L LC50 96 h <i>Lepomis macrochirus</i> static 6.75 - 14.5 mg/L LC50 96 h <i>Pimephales promelas</i> static 3.24 - 4.99 mg/L LC50 96 h <i>Pimephales promelas</i> flow-through 58.75 - 95.32 mg/L LC50 96 h <i>Poecilia reticulata</i> static
Diethylene glycol	75200 mg/L LC50 96 h <i>Pimephales promelas</i> flow-through
Talc	100 g/L LC50 96 h <i>Brachydanio rerio</i> semi-static
Methyl Methacrylate	243 - 275 mg/L LC50 96 h <i>Pimephales promelas</i> flow-through 79 mg/L LC50 96 h <i>Oncorhynchus mykiss</i> static 170 - 206 mg/L LC50 96 h <i>Lepomis macrochirus</i> flow-through 79 mg/L LC50 96 h <i>Oncorhynchus mykiss</i> flow-through 125.5 - 190.7 mg/L LC50 96 h <i>Pimephales promelas</i> static 326.4 - 426.9 mg/L LC50 96 h <i>Poecilia reticulata</i> static 153.9 - 341.8 mg/L LC50 96 h <i>Lepomis macrochirus</i> static
2-Hydroxyethyl methacrylate	213 - 242 mg/L LC50 96 h <i>Pimephales promelas</i> flow-through 227 mg/L LC50 96 h <i>Pimephales promelas</i>
Silica, Amorphous	5000 mg/L LC50 96 h <i>Brachydanio rerio</i> static

Chemical Name	Crustacea
Styrene	3.3 - 7.4 mg/L EC50 48 h Daphnia magna
Diethylene glycol	84000 mg/L EC50 48 h Daphnia magna
Methyl Methacrylate	69 mg/L EC50 48 h Daphnia magna
Silica, Amorphous	7600 mg/L EC50 48 h Ceriodaphnia dubia

Chemical Name	Algae/aquatic plants
Styrene	0.46 - 4.3 mg/L EC50 72 h Pseudokirchneriella subcapitata static 0.15 - 3.2 mg/L EC50 96 h Pseudokirchneriella subcapitata static 1.4 mg/L EC50 72 h Pseudokirchneriella subcapitata 0.72 mg/L EC50 96 h Pseudokirchneriella subcapitata
Methyl Methacrylate	170 mg/L EC50 96 h Pseudokirchneriella subcapitata
Silica, Amorphous	440 mg/L EC50 72 h Pseudokirchneriella subcapitata

Persistence and degradability No information available.

Bioaccumulative potential

Chemical Name	Partition coefficient
Styrene	2.95
Diethylene glycol	-1.98
Methyl Methacrylate	0.7
2-Hydroxyethyl methacrylate	0.47

Mobility

Mobility in soil

No information available.

Mobility

No information available.

Other adverse effects

Endocrine Disruptor Information.

Chemical Name	EU-Endocrine Disruptors Candidate List	EU-Endocrine Disruptors – Evaluated Substances	Endocrine Disrupting potential
Styrene	Group 1 Chemical	High Exposure Concern	-

Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products

Hazardous wastes must be transported by a licensed hazardous waste transporter and disposed of or treated in a licensed hazardous waste treatment, storage, disposal or recycling facility.

Contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations. Observe all label precautions until container is cleaned, reconditioned or destroyed. Refer to all federal, state and local regulations prior to disposal of container and unused contents by reuse, recycle or disposal.

Section 14: TRANSPORT INFORMATION

ADG

UN Number	UN1866
Proper shipping name	Resin solution
Description	UN1866, Resin solution, 3, III
Hazard Class	3
Packing Group	III
Special Provisions	223,*
Hazchem code	•3Y
IERG	14

IMDG

UN/ID no	UN1866
Proper shipping name	Resin solution
Description	UN1866, Resin solution, 3, III, (27°C c.c.)
Hazard Class	3
Packing Group	III
EmS-No	F-E, S-E
Special Provisions	223, 995

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

IATA

UNIID no	UN1866
Proper shipping name	Resin solution
Description	UN1866, Resin solution, 3, III
Hazard Class	3
Packing Group	III
ERG Code	3L

Section 15: REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations****Australia**

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG)" Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonised System (GHS)

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number

S6

Major hazard (accident/incident planning) regulation Verify that license requirements are met**Hazardous chemical category****Threshold quantity (T)**

Liquids that meet the criteria for Class 3 Packing Group II or III

50 000

Liquids with flash points <61°C kept above their boiling points at ambient conditions

200

Banned and/or restricted

This product contains one or more substances subject to prohibition, authorization or restriction. Veify that requirements related to using, handling and storing substances subject to prohibition, authorization or restriction are met.

Chemical Name	Carcinogen	Restricted Substance
Crystalline silica – 14808-60-7		For abrasive blasting at a concentration of >1%

International Inventories**AICS** - Australian Inventory of Chemical Substances

Listed or exempt

DSL - Canadian Domestic Substances List

Listed or exempt

IECSC - China Inventory of Existing Chemical Substances

Listed or exempt

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Listed or exempt Notified Chemical Substances**ENCS** - Japan Existing and New Chemical Substances

Not listed

KECI - Korean Existing and Evaluated Chemical Substances

Listed or exempt

NZIoC - New Zealand Inventory of Chemicals

Listed or exempt

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Listed or exempt

CICR - Turkey Chemical Inventory Control Regulation

No information available

NCSR - Taiwan National Chemical Substance Registry

No information available

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Listed or exempt

For confirmation on the European Reach status contact the FGA Regional Compliance group for additional information

International Regulations

Ozone-depleting substances (ODS) Not applicable
Persistent Organic Pollutants Not applicable
Export Notification requirements Not applicable

Section 16: ANY OTHER RELEVANT INFORMATION

Revision Date 19-Oct- 2016

Revision Note The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet