

**SAFETY DATA SHEET**

ISSUED DATE: 10th November 2016

Revision Date 19-Oct- 2016

Version 1

**Section 1: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY**

Product Identifier

Product Name **Neutral Spray Plastigel/Gelcoat**

Other means of identification

UN Number **UN1866**

Recommended use of the chemical and restrictions on use.

Recommended Use **Recommended for Industrial and/or Professional use only**

**Details of Distributor**

Fiberglass (A/Asia) Sales Pty. Ltd.  
2 Lincoln Street,  
Minto NSW 2566

For further information, please contact

Contact Point Phone: (02) 9820 1144

Email: [info@fiberglass-sales.com.au](mailto:info@fiberglass-sales.com.au)

Emergency Phone: (02) 9820 1144 (Business Hours)

**Section 2: HAZARD(S) IDENTIFICATION**

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG)

Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonised System (GHS)

**GHS Classification**

Flammable liquids	Category 3 - (H226)
Aspiration toxicity	Category 1 -(H304)
Acute toxicity - Oral	Category 4 -(H302)
Acute toxicity -Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1 - (H317)
Carcinogenicity	Category 1A -(H350)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)

Label elements



Signal word

Danger

**Hazard statements**

H226 - Flammable liquid and vapour  
 H302 - Harmful if swallowed  
 H332 - Harmful if inhaled  
 H315 - Causes skin irritation  
 H319 - Causes serious eye irritation  
 H317 - May cause an allergic skin reaction  
 H350 - May cause cancer  
 H361 - Suspected of damaging fertility or the unborn child  
 H335 - May cause respiratory irritation  
 H372 - Causes damage to organs through prolonged or repeated exposure  
 H304 - May be fatal if swallowed and enters airways

**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Use only outdoors or in a well-ventilated area  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Do not breathe dust/fume/gas/mist/vapours/spray  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 Specific treatment (see supplemental first aid instructions on this label)  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before re-use  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Rinse mouth  
 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other hazards**

Harmful to aquatic life with long lasting effects  
 Toxic to aquatic life  
 This product contains crystalline silica (quartz) in a non-repairable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product  
 Avoid dust formation  
 Sanding and grinding dust may be harmful if inhaled

**Section 3: COMPOSITION/INFORMATION ON INGREDIENTS****Substance**

Not applicable

**Mixture****Chemical Name****CAS No****Weight-%**

Styrene

100-42-5

30-&lt;60

Kaolin

1332-58-7

10-&lt;25

Titanium dioxide

13463-67-7

10-&lt;20

Diethylene glycol	111-46-6	10-<20
Talc	14807-96-6	10-<20
Methyl Methacrylate	80-62-6	5-<10
Silica gel, precipitated, crystal free	112926-00-8	1-<5
2-Hydroxyethyl methacrylate	868-77-9	1-<3
Silica, Amorphous	7631-86-9	1-<3
Cobalt octoate	136-52-7	<0.3
2-Hydroxy-4-methoxybenzophenone	131-57-7	<0.3
Dicocodimethylammonium chloride	61789-77-3	<0.3
Non-hazardous ingredients	Proprietary	Balance

## Section 4: FIRST AID MEASURES

### Description of first aid Measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. IF exposed or concerned: Get medical advice/attention.
<b>Emergency telephone number</b>	Poisons Information Centre, Australia: 13 11 26
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.
<b>Skin contact</b>	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Get medical attention if irritation develops and persists. Wash off immediately with soap and plenty of water for at least 15 minutes.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a doctor. Immediate medical attention is required. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Burning sensation.
-----------------	---

### Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	May cause sensitisation in susceptible persons. Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances
------------------------	---

## Section 5: FIRE FIGHTING MEASURES

**Suitable extinguishing media** Carbon dioxide (CO<sub>2</sub>). Dry chemical. Alcohol resistant foam. Water spray.

**Unsuitable extinguishing media** Do not use water jet stream.

### Specific hazards arising from the chemical

In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact. Thermal decomposition can lead to release of irritating and toxic gases and vapours. Flammable. Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.

**Special protective actions for fire-fighters**

Wear self-contained breathing apparatus and protective suit. Use personal protective equipment as required.

Hazchem code

• 3Y.

**Section 6: ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures****Personal precautions**

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders**

Use personal protection recommended in Section 8.

**Environmental precautions**

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

**Methods and material for containment and cleaning up****Methods for containment**

Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up.**

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

**Precautions to prevent secondary hazards****Prevention of secondary hazards**

Clean contaminated objects and areas thoroughly observing environmental regulations.

**Reference to other sections**

See section 8 for more information. See section 13 for more information.

**Section 7: HANDLING AND STORAGE****Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before re-use. Remove contaminated clothing and shoes.

**General Hygiene Considerations**

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash hands before breaks and immediately after handling the product. Wash hands before breaks and after work. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

**Conditions for safe storage, including any incompatibilities****Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e. pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep out of the reach of children. Store locked up. Store away from other materials. Hazardous polymerisation may take place during a fire due to heat. Closed containers could violently rupture. Do not store at temperatures above 27C.

**Incompatible materials**

Strong acids. Strong bases. Strong oxidising agents.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

**Exposure Limits** This product, as supplied, contains hazardous materials with occupational exposure limits.

Chemical Name	Australia
Styrene 100-42-5	50 ppmTWA 213 mg/m <sup>3</sup> TWA 100 ppm STEL 426 mg/m <sup>3</sup> STEL
Kaolin 1332-58-7	10 mg/m <sup>3</sup> TWA
Titanium dioxide 13463-67-7	10 mg/m <sup>3</sup> TWA
Diethylene glycol 111-46-6	23 ppmTWA 100 mg/m <sup>3</sup> TWA
Talc 14807-96-6	2.5 mg/m <sup>3</sup> TWA
Methyl Methacrylate 80-62-6	50 ppm TWA 208 mg/m <sup>3</sup> TWA 100 ppm STEL 416 mg/m <sup>3</sup> STEL
silica gel, precipitated, crystal free 112926-00-8	10 mg/m <sup>3</sup> TWA
Silica, Amorphous 7631-86-9	2 mg/m <sup>3</sup> TWA

### Biological occupational exposure limits

An occupational medicine specialist familiar with national and regional regulations and standards must be consulted to establish a program of medical examinations for workers exposed to substances with biological limit values

Chemical Name	Australia	ACGIH	United Kingdom	European Union
Styrene 100-42-5	-	Mandelic acid plus phenylglyoxylic acid: 400 mg/g creatinine urine end of shift Styrene: 40 µg/L urine end of shift	-	

### Appropriate engineering controls

**Engineering Controls** Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles. Face protection shield.

**Skin and body protection** Antistatic footwear. Wear fire flame resistant/retardant clothing. Gloves made of plastic or rubber. Suitable protective clothing. Apron.

**Respiratory protection** Where respiratory protection is required, use a respirator selected and in accordance with AS/NZS 1715 and AS/NZS 1716.

**Environmental exposure controls** Do not allow into any sewer, on the ground or into any body of water.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Clear Hazy
Colour	Clear
Odour	Pungent
Odour threshold	No information available

Property	Values	Remarks • Method
pH		Not applicable
Melting point / freezing point		No information available
Boiling point / boiling range	145°C	(based on components)
Flash point	27°C	Tag Closed Cup
Evaporation rate	0.49	

<b>Flammability (solid, gas)</b>		No information available
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	6.1%	
<b>Lower flammability limit:</b>	1.1%	
<b>Vapour pressure</b>	6	hPa, 20°C Derived from solvent
<b>Vapour density</b>	3.6	Derived from solvent
<b>Relative density</b>	0.95	
<b>Water solubility</b>		Insoluble
<b>Solubility(ies)</b>	-	No information available
<b>Partition coefficient</b>		No information available
<b>Autoignition temperature</b>		No information available
<b>Decomposition temperature</b>		No information available
<b>Kinematic viscosity</b>		No information available
<b>Dynamic viscosity</b>		No information available
<b>Explosive properties</b>	No information available	
<b>Oxidising properties</b>	Not applicable	

### Other Information

<b>VOC Content (%)</b>	Not applicable
<b>Density</b>	No information available
• This information may be derived from the components in the preparation.	

## **Section 10: STABILITY AND REACTIVITY**

<b><u>Reactivity</u></b>	No Data Available.
<b><u>Chemical stability</u></b>	Stable under normal conditions.
<b><u>Explosion data</u></b>	
Sensitivity to Mechanical Impact	None
Sensitivity to Static Discharge	May be ignited by heat, sparks or flames.
<b><u>Possibility of Hazardous Reactions</u></b>	
HAZARDOUS POLYMERISATION MAY OCCUR UPON DEPLETION OF INHIBITOR.	
<b><u>Conditions to avoid</u></b>	
Heat, flames and sparks.	
<b><u>Incompatible materials</u></b>	
Strong acids. Strong bases. Strong oxidising agents.	
<b><u>Hazardous Decomposition Products</u></b>	
Decomposition products can include and are not limited to: Styrene.	

## **Section 11: TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

#### **Information on likely routes of exposure**

#### **Product Information**

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Irritating to eyes. (based on components). Causes serious eye irritation.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Repeated exposure may cause skin dryness or cracking.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. (based on components).

#### **Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

Converted acute toxicity point estimates may have been used when only acute toxicity hazard classification is available.

ATEmix (oral)	1,413.00
ATEmix (dermal)	82,543.00
ATEmix (inhalation-vapour)	27.00
ATEmix (inhalation-dust/mist)	3.70
0 of the mixture consists of ingredient(s) of unknown toxicity	

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene	= 1000 mg/kg (Rat)	-	= 11.7 mg/L (Rat) 4 h
Diethylene glycol	= 12565 mg/kg (Rat)	- 11890 mg/kg (Rabbit)	-
Methyl Methacrylate	= 7900 mg/kg (Rat) = 7872 mg/kg (Rat)	-	- 4632 ppm (Rat) 4 h
2-Hydroxyethyl methacrylate	= 5050 mg/kg (Rat)	-	-
2-Hydroxy-4-methoxybenzophe None	= 7400 mg/kg (Rat)	-	-

See section 16 for terms and abbreviations

### **Delayed and immediate effects as well as chronic effects from short and long-term exposure**

#### **Skin corrosion/irritation**

Classification based on data available for ingredients. Irritating to skin.

#### **Serious eye damage/eye irritation**

Classification based on data available for ingredients. Irritating to eyes.

#### **Sensitisation**

May cause sensitisation by skin contact

#### **Germ cell mutagenicity**

No information available.

#### **Carcinogenicity**

Chemical Name	Australia	IARC
Styrene - 100-42-5		Group 2B
Titanium dioxide - 13463-67-7		Group 2B
Talc - 14807-96-6		Group 3
Methyl Methacrylate - 80-62-6		Group 3
Silica gel, precipitated, crystal free - 112926-00-8		Group 3
Silica, Amorphous - 7631-86-9		Group 3
Cobalt octoate - 136-52-7		Group 2B

#### **IARC (international Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

#### **Reproductive toxicity**

Classification based on data available for ingredients. Contains a known or suspected reproductive toxin. The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

#### **STOT - single exposure**

May cause respiratory irritation.

#### **STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

## **Section 12: ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

##### **Unknown Aquatic Toxicity**

0.07638083 of the mixture consists of components(s) of unknown hazards to the aquatic environment



Chemical Name	Fish
Styrene	19.03 - 33.53 mg/L LC50 96 h <i>Lepomis macrochirus</i> static 6.75 - 14.5 mg/L LC50 96 h <i>Pimephales promelas</i> static 3.24 - 4.99 mg/L LC50 96 h <i>Pimephales promelas</i> flow-through 58.75 - 95.32 mg/L LC50 96 h <i>Poecilia reticulata</i> static
Diethylene glycol	75200 mg/L LC50 96 h <i>Pimephales promelas</i> flow-through
Talc	100 g/L LC50 96 h <i>Brachydanio rerio</i> semi-static
Methyl Methacrylate	243 - 275 mg/L LC50 96 h <i>Pimephales promelas</i> flow-through 79 mg/L LC50 96 h <i>Oncorhynchus mykiss</i> static 170 - 206 mg/L LC50 96 h <i>Lepomis macrochirus</i> flow-through 79 mg/L LC50 96 h <i>Oncorhynchus mykiss</i> flow-through 125.5 - 190.7 mg/L LC50 96 h <i>Pimephales promelas</i> static 326.4 - 426.9 mg/L LC50 96 h <i>Poecilia reticulata</i> static 153.9 - 341.8 mg/L LC50 96 h <i>Lepomis macrochirus</i> static
2-Hydroxyethyl methacrylate	213 - 242 mg/L LC50 96 h <i>Pimephales promelas</i> flow-through 227 mg/L LC50 96 h <i>Pimephales promelas</i>
Silica, Amorphous	5000 mg/L LC50 96 h <i>Brachydanio rerio</i> static

Chemical Name	Crustacea
Styrene	3.3 - 7.4 mg/L EC50 48 h <i>Daphnia magna</i>
Diethylene glycol	84000 mg/L EC50 48 h <i>Daphnia magna</i>
Methyl Methacrylate	69 mg/L EC50 48 h <i>Daphnia magna</i>
Silica, Amorphous	7600 mg/L EC50 48 h <i>Ceriodaphnia dubia</i>

Chemical Name	Algae/aquatic plants
Styrene	0.46 - 4.3 mg/L EC50 72 h <i>Pseudokirchneriella subcapitata</i> static 0.15 - 3.2 mg/L EC50 96 h <i>Pseudokirchneriella subcapitata</i> static 1.4 mg/L EC50 72 h <i>Pseudokirchneriella subcapitata</i> 0.72 mg/L EC50 96 h <i>Pseudokirchneriella subcapitata</i>
Methyl Methacrylate	170 mg/L EC50 96 h <i>Pseudokirchneriella subcapitata</i>
Silica, Amorphous	440 mg/L EC50 72 h <i>Pseudokirchneriella subcapitata</i>

**Persistence and degradability** No information available.

**Bioaccumulative potential**

Chemical Name	Partition coefficient
Styrene	2.95
Diethylene glycol	-1.98
Methyl Methacrylate	0.7
2-Hydroxyethyl methacrylate	0.47

**Mobility**

**Mobility in soil**

No information available.

**Mobility**

No information available.

**Other adverse effects**

Endocrine Disruptor Information.

Chemical Name	EU-Endocrine Disruptors Candidate List	EU-Endocrine Disruptors – Evaluated Substances	Endocrine Disrupting potential
Styrene	Group 1 Chemical	High Exposure Concern	-

**Section 13: DISPOSAL CONSIDERATIONS**

**Waste treatment methods**



<b>Waste from residues/unused products</b>	Hazardous wastes must be transported by a licensed hazardous waste transporter and disposed of or treated in a licensed hazardous waste treatment, storage, disposal or recycling facility.
<b>Contaminated packaging</b>	Disposal should be in accordance with applicable regional, national and local laws and regulations. Observe all label precautions until container is cleaned, reconditioned or destroyed. Refer to all federal, state and local regulations prior to disposal of container and unused contents by reuse, recycle or disposal.

## Section 14: TRANSPORT INFORMATION

### ADG

UN Number	UN1866
Proper shipping name	Resin solution
Description	UN1866, Resin solution, 3, III
Hazard Class	3
Packing Group	III
Special Provisions	223,*
Hazchem code	•3Y
IERG	14

### IMDG

UN/ID no	UN1866
Proper shipping name	Resin solution
Description	UN1866, Resin solution, 3, III, (27°C c.c.)
Hazard Class	3
Packing Group	III
EmS-No	F-E, S-E
Special Provisions	223, 995

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

### IATA

UNIID no	UN1866
Proper shipping name	Resin solution
Description	UN1866, Resin solution, 3, III
Hazard Class	3
Packing Group	III
ERG Code	3L

## Section 15: REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations**  
**Australia** Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG)" Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonised System (GHS)

### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

**Poison Schedule Number** S6

**Major hazard (accident/incident planning) regulation** Verify that license requirements are met

Hazardous chemical category	Threshold quantity (T)
Liquids that meet the criteria for Class 3 Packing Group II or III	50 000
Liquids with flash points <61°C kept above their boiling points at ambient conditions	200

Chemical Name	National pollutant inventory
Styrene - 100-42-5	10 tone/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tone/h Threshold category 2a total 25 tone/yr Threshold category 1a total 400 tone/yr Threshold category 2a total 2000 tone/yr Threshold category 2b total
Diethylene glycol - 111-46-6	60000 MWH Threshold category 2b total 1 tone/h Threshold category 2a total 25 tone/yr Threshold category 1a total 400 tone/yr Threshold category 2a total 2000 tone/yr Threshold category 2b total
Methyl Methacrylate - 80-62-6	60000 MWH Threshold category 2b total 1 tone/h Threshold category 2a total 25 tone/yr Threshold category 1 a total 400 tone/yr Threshold category 2a total 2000 tonnellyr Threshold category 2b total
Cobalt octoate - 136-52-7	10 tone/yr Threshold category 1

International Inventories

<b>AICS</b> - Australian Inventory of Chemical Substances	Listed or exempt
<b>DSL</b> - Canadian Domestic Substances List	Listed or exempt
<b>IECSC</b> - China Inventory of Existing Chemical Substances	Listed or exempt
<b>EINECS/ELINCS</b> - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances	Listed or exempt
<b>ENCS</b> - Japan Existing and New Chemical Substances	Not listed
<b>KECI</b> - Korean Existing and Evaluated Chemical Substances	Listed or exempt
<b>NZIoC</b> - New Zealand Inventory of Chemicals	Listed or exempt
<b>PICCS</b> - Philippines Inventory of Chemicals and Chemical Substances	Listed or exempt
<b>CICR</b> - Turkey Chemical Inventory Control Regulation	No information available
<b>NCSR</b> - Taiwan National Chemical Substance Registry	No information available
<b>TSCA</b> - United States Toxic Substances Control Act Section 8(b) Inventory	Listed or exempt

For confirmation on the European Reach status contact the FGA Regional Compliance group for additional information

International Regulations

<b>Ozone-depleting substances (ODS)</b>	Not applicable
<b>Persistent Organic Pollutants</b>	Not applicable
<b>Export Notification requirements</b>	Not applicable

<b>Section 16: ANY OTHER RELEVANT INFORMATION</b>
---

**Revision Date** 19-Oct- 2016

**Revision Note** The symbol (\*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**